

SPECIFICATIONS :

Voltage Rating: 250V AC / DC
 Current Rating: 5A AC / DC
 Withstanding Voltage: 1000V AC/minute
 Temperature Range: -40°C~+105°C
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 10mΩ Max.
 *Mates with LDZY C3030HF series Double Row Housing



Material:

Wafer: LCPUL94V-0,Black
 Conductor: Brass/Tin-Plated.

C3030 W R F - 2NP - XX BK X X
 ① ②③④ ⑤ ⑥ ⑦ ⑧⑨

- ① Series No.
- ② Category: W-wafer
- ③ Welding Board Angle: V- Straight 180° R-Vertical 90°
- ④ Colloid Feature: ,F-Double location column
- ⑤ Circuit No.: 202-2x1PIN....224-2*12P
- ⑥ Material: L0-LCP,UL94V-0;
- ⑦ Color: BK-Black
- ⑧ Plating Method: T-Tin-plated, G-Gold-flash,G-Gold3u"
- ⑨ Option: Blank-Standard type(盘装, 10盘/扎)

Poles	Dimensions (mm)		
	A	B	C
2*01	---	6.65	3.55
2*02	3.00	9.65	3.55
2*03	6.00	12.65	3.55
2*04	9.00	15.65	8.30
2*05	12.00	18.65	11.30
2*06	15.00	21.65	14.30
2*07	18.00	24.65	17.30
2*08	21.00	27.65	20.30
2*09	24.00	30.65	23.30
2*10	27.00	33.65	26.30
2*11	30.00	36.65	29.30
2*12	33.00	39.65	32.30

2023-2-25	A	B	统一盘装			一般公差 GENERAL TOLERANCE .X ±0.30 .XX ±0.20 .XXX ±0.10	 LDZY® 东莞市蓝雁电子有限公司 Electroni DongGuan LDZY Electronics CO.,LTD.	料号 PART NO C3030WRF-2NP-XXBKXX						
2019-2-25		A	新模			角法 PROJECT 		核准 APPD	审核 CHK	绘图 DR	日期 DATA	品名 TITLE MX 3.00mm Dual Row 90° DIP Wafer针座		
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION	审核 CHK	核准 APPD		周立鸿	兰雄	唐文舜	2020/07/23	单位 UNIT mm	比例 SCALE 1/1	图号 NUMBER LDZY-8802	版次 REV B